




Kalamazoo Machine Tool

Models H6A-NC and H6 SA Double column mitering bandsawing machines. Both feature a canted (6 degrees) sawframe. Mitering from 0-60 degrees. All functions are fully hydraulic, with free-standing operators console that may be conveniently placed in the most advantageous operator location. Sawfeed controls are done with precision control valves.



H6 A-NC

The **H6A-NC** barfeed is a true shuttle-vice machine. The machine is fully programmable to automatically program and store jobs for later recall. Two saw vises on the infeed side ensure the material is clamped and never released during all feeding and sawing operations. Barfeeder travels on linear guides, and driven by heavy duty ball screw for maximum accuracy. Both feeder vise jaws clamp & unclamp, to facilitate crooked material. Scrap remnant end; a short 4" Operation is straightforward and logical. The machine may be used as a single cut (semi-automatic) or fully automatic machine to repetitively cut your material to length. You program the length, size of material, blade speed and quantity at the keyboard.



H6 SA

| Specifications | H6 SA | H6 A-NC |
|----------------------|-------------|-------------|
| Blade Drive | 5HP | 7HP |
| Blade Speeds | 60-360 FPM | 60-360 FPM |
| Blade Size | 1¼ X 17' 5" | 1¼ X 17' 5" |
| Material Work Height | 32¼" | 32¼" |
| Vise Opening | 23½" | 23½" |
| Machine Weight | 4000 Lbs | 5100 Lbs |
| Footprint | 49" x 112" | 104" x 112" |
| Electricals | 3 Phase | 3 Phase |

| Capacity Chart | H6 SA | H6 A-NC |
|----------------|-------|---------|
| 90 Degrees | 20" | 20" |
| 45 Degrees | 17½" | 17½" |
| 60 Degrees | 9½" | 9½" |

Kalamazoo Machine Tool

6700 Quality Way * Portage, MI 49002

269-321-8860 * Fax 269-321-8890

www.kmtsaw.com